

ENEOS Import CVT Fluid

DESCRIPTION

ENEOS Import CVT Fluid is continuously variable transmission fluid engineered specifically for Asian vehicles from Honda, Acura and Nissan. ENEOS Import CVT Fluid is formulated with select high-quality synthetic base oils combined with unique additives developed through the advanced technology of JX Nippon Oil & Energy. JX Nippon Oil & Energy is the leading innovator and supplier of automotive lubricants to the majority of Asian automobile manufacturers. ENEOS Import CVT Fluid provides outstanding compatibility and performance for all of the service fill requirements for your vehicle applications ENEOS Import CVT Fluid is part of the **ENEOS Import Series**, which also include ATF and DPS fluids. For more information, please visit www.eneos.us/import-series.

APPLICATION

ENEOS Import CVT Fluid is recommended for uses in continuously variable transmissions where genuine fluids in the table below are specified.

	ENEOS Import CVT Fluid	
	MODEL H	MODEL N
Vehicle Maker	Honda, Acura	Nissan
Transmission	CVT ^{*1}	CVT ^{*1}
Genuine Fluid	Honda CVT FLUID, HCF-2	Nissan CVTF NS-2

*1: Continuously Variable Transmission

Note: Please consult your vehicle owners' manual for proper transmission fluid requirements. For further information, please refer to the Compatibility List on www.eneos.us/import-series.

TYPICAL PROPERTIES

ENEOS Import CVT Fluid

Test Item	MODEL H	MODEL N	Test Method
Color	Orange	Green	
Density (15°C) g/cm ³	0.850	0.853	ASTM D 4052
Viscosity mm ² /s			ASTM D 445
(40°C)	30.3	29.5	
(100°C)	6.57	6.48	
Viscosity Index	180	182	ASTM D 2270
BF Viscosity (-40°C) mPa·s	9700	9600	ASTM D 2983
Flash Point °C	230	208	ASTM D 92
Pour Point °C	-45	-45	ASTM D 97

Note: Typical Properties are test data to be expected in normal production and subject to change without notice.

ENEOS is the corporate brand name of JX Nippon Oil & Energy Corporation, the largest oil company in Japan. **ENEOS** brand is developed to exceed the highest standards of the automotive industry. **ENEOS** product ranges that offer optimal performance protection under the most extreme temperature variations, to ecologically friendly oil that provides superior fuel saving capacity. For more information please visit www.eneos.us.