

ENEOS Gear Oil LSD GL-5 75W-90

DESCRIPTION

ENEOS GEAR OIL LSD is fully synthetic gear oil using the latest technology that ensures superior performance in every area required of differential gears, including LSD (Limited Slip Differential). The base oil and additive technology in **ENEOS GEAR OIL LSD** assures excellent protection of the gears against metal-to-metal contact under the most severe conditions, including shock-loads.

APPLICATION

ENEOS GEAR OIL LSD is recommended for use in bevel, spiral bevel and hypoid gear type differentials. It is also compatible with synchromesh transmissions. The proprietary technology in **ENEOS GEAR OIL LSD** ensures easy and smooth shifting, even at very low temperatures.

Note: Please consult your vehicle owners' manual for proper transmission fluid requirements.

TYPICAL PROPERTIES

ENEOS Gear Oil LSD GL-5 75W-90

Test Item	Data	Test Method
API Grade	GL-5	
SAE Viscosity	75W-90	
Color	L1.5	
Density (15°C) g/cm ³	0.869	ASTM D 4052
Viscosity mm ² /s (40°C) (100°C)	88.6 14.5	ASTM D 445
Viscosity Index	171	ASTM D 2270
Flash Point °C	216	ASTM D 92
Foaming	10/0	ASTM D 892
Brook Field Viscosity (-40°C)	41,100	ASTM D 2983
Acid Number mgKOH/g	3.57	ASTM D 664

Note: Typical Properties are test data to be expected in normal production and subject to change without notice.

For more information, please visit www.eneos.us/products/eneos-gear-oil/.

ENEOS is the corporate brand name of **JX Nippon Oil & Energy Corporation**, the largest oil company in Japan. **ENEOS** is developed to exceed the highest standards of the automotive industry. **ENEOS** products offer optimal performance protection under the most extreme temperature variations, are ecologically friendly, and provide superior fuel saving capacity. For more information please visit www.eneos.us.