

ENEOS Gear Oil LSD GL-5 75W-90

DESCRIPTION

ENEOS GEAR OIL LSD is fully synthetic gear oil using the latest technology that ensures superior performance in every area required of differential gears, including LSD (Limited Slip Differential). The base oil and additive technology in **ENEOS GEAR OIL LSD** assures excellent protection of the gears against metal-to-metal contact under the most severe conditions, including shock-loads.

APPLICATION

ENEOS GEAR OIL LSD is recommended for use in bevel, spiral bevel and hypoid gear type differentials. It is also compatible with synchromesh transmissions. The proprietary technology in **ENEOS GEAR OIL LSD** ensures easy and smooth shifting, even at very low temperatures.

Note: Please consult your vehicle owners' manual for proper transmission fluid requirements.

TYPICAL PROPERTIES

ENEOS Gear Oil LSD GL-5 75W-90

Test Item	Data	Test Method
API Grade	GL-5	
SAE Viscosity	75W-90	
Color	L1.5	
Density (15°C) g/cm ³	0.869	ASTM D 4052
Viscosity mm ² /s		ASTM D 445
	(40°C) 88.6	
	(100°C) 14.5	
Viscosity Index	171	ASTM D 2270
Flash Point °C	216	ASTM D 92
Foaming	10/0	ASTM D 892
Brook Field Viscosity (-40°C)	41,100	ASTM D 2983
Acid Number mgKOH/g	3.57	ASTM D 664

Note: Typical Properties are test data to be expected in normal production and subject to change without notice.

ENEOS

Established in 1888 and headquartered in Tokyo, ENEOS is Japan's largest oil company, with manufacturing and sales facilities throughout the world. ENEOS has worked with Japan's automakers and leading race teams for decades, creating advanced lubricants with vehicle engineers to provide optimum fuel economy with maximum power and long-term protection. For more information please visit www.eneos.us.